

Side dump loader ŁBT-1200M

It is adapted to main work in conditions of methane explosion risk. It has telescoping loading arm, fixed on turntable. Used for loading output on cars and conveyors.

**BUMAR ŁABĘDY**

Zakłady Mechaniczne „BUMAR-ŁABĘDY” S.A.
ul. Mechaników 9
bumar@bumar.gliwice.pl
fax: +48 32 734 65 11

„BUMAR-ŁABĘDY” S.A.
44-109 GLIWICE
www.bumar.gliwice.pl
tel: +48 32 734 51 11



Side dump loader ŁBT-1200M

Main advantages:

- short time of shovel working cycle
- equipped with energy-saving system „load-sensing”
- works on max. slope gradient
- unloading of output on both sides of the loader
- very high movement parameters
- high force of digging into the output-heap
- the construction of the loader allows instalation of a platform for repairing crews which enables conservation works in mine corridors
- the platform is mounted on a loader bucket

Technical data:	
loader weight	14 500 kg
bucket capacity	1,2 m ³
driving speed	0-1 m/s
ground pressure unit	0,11 MPa
max. slope gradient	+/- 20°
motor	55 kW/500V
supply voltage	500V lub 1000V
control voltage	24V
track width	300 mm
electrical installation	according to directive 2006/42/WE (ATEX) Ex IM2
pumps performance	210 + 24 dm ³ /min
working pressure	18 MPa
oil tank capacity	400 dm ³